



L Series

L4802HST

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

#### DIESEL ENGINE

Model # V2403-CR-E4-LB1  
Tier 4 Final Engine  
Common Rail Direct Injection  
w/ Diesel Particulate Filter  
Electronic Throttle  
4 Cyl. 148.5 cu. in.  
+ 46.0 Net Eng. HP  
+ 40.5 PTO HP  
@ 2600 Eng. rpm  
12V, 600A CCA  
Charging Output 40 Amps  
Dual Air Cleaner Element

#### HYDRAULICS

Open Center  
Tandem Pumps Gear Type  
7.8 gpm Remote/3 Pt. Hitch  
4.7 gpm for Power Steering  
13.5 Total gpm  
Cat I 3-point Hitch  
At lift Point 2870 lb.  
24" Behind 2320 lb.

#### FRONT AXLE

Hydrostatic Power Steering  
Bevel Gear, Cast Iron  
Tread Spacing, nonadjustable

#### DASH INSTRUMENTS

Tachometer  
Fuel Gauge  
Temperature Gauge  
LCD Display for Hour Meter  
and Warning Messages

#### FLUID CAPACITY

Fuel Tank 13.5 gal.  
Cooling System 6.9 qts.  
Crankcase 8.7 qts.  
Transmission and  
Hydraulics 10.6 gal.  
Front Axle 6.9 qts.

#### DIMENSIONS

Overall Height w/ROPS 91.7"  
Overall Length w/3pt 127.4"  
Wheel Base 72.8"  
Crop Clearance 16.1"

#### POWER TAKE OFF

Live Independent Hydraulic PTO  
w/ hydraulic clutch  
540 rpm Rear PTO – 1 Speed  
Speed - 540 @ 2475 Eng. rpm  
SAE Std 1 3/8" Six Spline

#### SAFETY EQUIPMENT

Foldable ROPS w/ Retractable Seat

DRIVE TRAIN	Belt
Synchro Shuttle with Sliding Gear	PTO Shield
Shift Transmission	Safety Start Switches
8 Forward Speeds	Turn Signals / Hazard Lights
8 Reverse Speeds	Mechanical Wet Disc Brakes
Multiple Wet Disc Brakes	Parking Brakes
Clutch – Dry Type Single Stage	SMV Sign
Differential Lock	Electric Key Shut-off
Rear Axle – Spur Gear	Parking Brake Indicator on Dash
	Operator Presence Control System

+ Manufacturer Estimate

OPERATOR STATION

- Color Coded Controls
- Wide Platform Steps
- High Back Seat with Adjustable Suspension w/ Water Drain Hole
- Tool Box
- Cup Holder
- Left Hand Fender Grip
- Default to Auto Regen; w/ Parked and Inhibit Buttons for DPF

## TIRES AND WHEELS

Front 8.3 - 16 R1

Rear 14.9 - 24 R1